







FOR HARSH ENVIRONMENTS

The SEL Series permanent rack and pinion industrial lifts are suitable for both indoor and outdoor use. They are designed to reach the highest heights and ensure safe and efficient vertical transport of persons, tools and equipment. On request, Fraco can customize car sizes, speed, payload and finish to meet location restrictions. Inclined mast sections are available for special projects.

All models are manufactured with non-proprietary electrical and mechanical components that are available from local suppliers. The SEL Series is characterized by the integration of variable frequency converters or PLC based control system. Each model uses flexible wall ties and adjustable turnbuckles.

If required, elevators can conform to explosion proof requirements (Class 1 and Class 2). Other options such as emergency descent, automatic greasing device and firemen recall system are also available.

Since they are manufacturerd in North America, SEL Series elevators are supported by the best response time for service parts. All models are fully compliant with ANSI A17.1 and CSA B44 standards.

TECHNICAL DATA	WIDTH	LENGHT	HEIGHT	PERSONS	PAYLOAD	DRIVE	SPEED
SEL-500	2 FT 7 IN	2 FT 7 IN	7 FT	3	500 LB	VFC OR DOL	0-98 FT / MIN 0-130 FT / MIN 0-198 FT / MIN 0-300 FT / MIN
SEL-750	2 FT 7 IN	3 FT 6 IN	7 FT	4	750 LB		
SEL-1000	3 FT 6 IN	3 FT 6 IN	7 FT	6	1 000 LB		
SEL-1500	3 FT 6 IN	5 FT 6 IN	7 FT	8	1 500 LB		
SEL-2000	3 FT 6 IN	6 FT 6 IN	7 FT	10	2 000 LB		
SEL-2500	3 FT 6 IN	8 FT	7 FT	14	2 500 LB		
SEL-3000	4 FT 9 IN	7 FT	7 FT	16	3 000 LB		
SEL-4000	4 FT 9 IN	8 FT 6 IN	7 FT	20	4 000 LB		
SEL-5000	4 FT 9 IN	10 FT 6 IN	7 FT	24	5 000 LB		
SEL-6000	4 FT 9 IN	12 FT	7 FT	28	6 000 LB		
SEL-7000	4 FT 9 IN	13 FT 6 IN	7 FT	32	7 000 LB		



- + 1 800 267.0094
- + 1 450 658.0094
- + 1888 372,2648